



8900 North 55th Street ▪ Milwaukee, WI ▪ 53224-9540 ▪ 414-354-0300 ▪ (fax) 414-354-7905

ORIGINS

¼” CUSTOM INSERT PANEL SIZES

BI-95	13 15/32” H x 12 15/16” W
BI-98	15 15/16”H x 13 15/16” W
29 Series	21 13/32” H x 19 13/16” W
75 Series	28 5/32” H x 22 15/16” W
75 Stainless Series	29 13/32” H x 22 15/16”W
1115 Series	26 15/16” H x 13 15/16” W
1175 Series	26 15/16” H x 22 15/16” W

- Zero clearance with a flush/flat door panel.
- Door will accept a raised panel. Allow proper clearance, on hinge side when installing a raised panel. Amount of clearance will depend on raised panel thickness.
- The maximum panel thickness when inserted into the door reveal (channel) is ¼” thick.
- For raised panels on BI 95, BI98, 29 series and 75 series models the depth of the reveal is ¼” on both sides and bottom and ½” on top.
- For raised panels on 75 Stainless, 1115, and 1175 series models the depth of the reveal is ¼” on both sides, bottom, and top.
- Allow 9/16” clearance on hinge side for 75 Stainless models with a flush/flat panel. Additional clearance may be needed on hinge side when installing a raised panel. Amount of clearance will depend on raised panel thickness.
- Panel not to exceed 20 pounds.
- Conversion information: 1 inch = 2.54 cm